

All Flex Mowers

AFM4211 Models

Features	Benefits
Counter blade rotation on left hand deck	Spreads grass clippings more evenly. Wing decks throw grass away from the rear deck. Rear deck doesn't get covered up nor does it get bogged down by cut grass.
7'-8" transport width at lowest cutting height	Meets most city/county codes for transport width.
6" Deck overlap	Eliminates skipping when going into a tight turn.
11'-1" Cutting width – three 48" decks	Sized right for golf courses, cities, schools. Small decks give excellent flexibility.
Sleek frame design, including single beam hitch and compact deck overlap	Design allows operator to make tighter turns without leaving windrows and skips. AFM virtually becomes a zero turn mower. (Oversized tires may not allow this.)
Automatic transport wing locks	When wings are raised in the full transport position, the wings lock in place. No need to get off the tractor to lock. Pull rope from tractor seat to un-lock.
18" Transport tires with tapered roller bearings	Transport tires offer smooth roading and less grass compaction. Allows grass to stand up. Tapered roller bearings offer longevity.
Removable transportation tire spindles	Allows a spindle to be replaced by simply removing two bolts.
Back wheels on side decks even with transportation tires	Allows tighter turns without skips.
Rigid rear side deck tires.	Rigid wheel yokes holds hills and slopes better. Safer unit than the competition.
13" Deck tires with sealant	13" Tires offer great flotation, less lbs. per square inch. Sealant minimizes flats.
1/4" Gauge wheel arms	Gives the cutter gauge wheel arms a great deal of "hidden" strength.
Low pivot points on deck	The lower the pivot points are to the ground, the more side to side swing, allowing for excellent flotation from each deck.
Deflectors built into mower decks	Safety features meet ANSI standards. Many competitors use chains for protection. Once chains are removed the unit does not meet ANSI specifications.
Rear discharge	Even dispersal, discharged items are aimed downward. No rear chains are needed, which tend to clump damp grass.
Rounded front deck edges with no protruding skid shoe	Helps protect trees and other obstacles.
5/16" Front edge & all-welded seams	Provides extra durability.
Cat. 3 Constant velocity main driveline	Constant velocity main driveline allows for tighter turns without harming U-joints in driveline, includes slip clutch option.
Cat. 2 wing drivelines	Reduces start-up torque that is put on the driveline, gearbox and gearbox support.
Slip-clutch protection	Guards against premature gearbox failure. Protects mower deck spindles.
ABS guards	No paint to scratch off, lighter weight, no rattling or rust.
Heavy gearbox mounts on center and side mower decks	Handles start-up torque better.
Gearbox HP Rating	30 -65 HP
Gearbox warranty	5 years on parts and labor. Demonstrates our confidence in the gearbox's quality and lasting performance.
Easy to grease blade spindles	No guards to remove for routine greasing of blade spindles.
Middle spindle sits towards the back of the mower deck.	Uses less horsepower and allows material to escape the mower deck easier. The discharge of material is more even. Design eliminates windrowing.
Spring loaded idlers	Applies constant tension to belt to run efficiently.
Easy belt tension release	Easily release belt tension for changing belt or for winter storage.
High blade tip speed	(16,260 fpm) Lifts grass up for a clean cut and efficient discharge of material. Tip speed rates are as high or higher than the competition.
Choice of Blade (Medium lift standard) Others available thru parts dept.	Low Lift - Highly recommended in sandy soils where lifting isn't crucial. Disturbs the soil very little, allowing blades to wear longer. Medium Lift - Medium suction for lifting grass. Requires less HP than high lift. High Lift - Greatest suction for lifting grass before cutting. Can take higher HP in tall dense grass. Not recommended in sandy soils. Mulching - Perfect for leaf mulching.
Optional Hydraulic Operated Transport Locks	Transports locks can be released easily from the tractor seat while operating the same tractor control lever that raises and lowers the mower decks. Eliminates pulling a rope to release transport locks.

Designs, specifications, features and information are subject to change without notice.