

Automatic wing locks for transport

· Zero turning radius due to sleek frame design

- · Rear discharge for even dispersal
- · Easy to grease from top blade spindles



Dispensing cut grass is a key ingredient to maintaining healthy turf. The more evenly and completely the cut grass is dispersed, the quicker it works its way towards the soil for decomposition.

AFM42 Series

30-65 HP AFM4211 Pull-Type Hitch, Adjustable Clevis

Working Width (cm) 11'1" (338)

Overall Width 11'3-1/2"

Transport Width 7'8"

Positive Tongue Wt - lb 450

Weight - Ib (kg) 2040 (918)

Cutting Height 1" - 5-1/2" in 1/2" incr.

Wing Cylinders 2-1/2" x 12"

Rear Deck Cylinder 2" x 8" 540 RPM, 3 wing,

Gearbox 1 splitter

Decks: 3 each 48"

Deck Thickness 3/16"

Deck Overlap 6"

Blade Hub 4 bolt casting

Blade Size 1/4" x 2-1/2" x 16-3/4"

Blade Overlap 1-3/16"

Blade Tip Speed 16,260 fpm (184 mph)

Blade Bearings Greaseable ball bearings

Spindle Bearing Dia. 1-3/16"

Blade Spindle RPM 3,668 RPM

Blade Drive Belt 1 B-section

Discharge Rear

Deck Tires - 10 ea. 13 x 5 Air Tire, Sealant

Deck Wheel Spindles 1-1/4" w/Nylon Bushings

Transport Tires and 18 x 9.5, Sealant and

Bearing Tapered Bearings

Anti-Scalp Roller Front Center

and Outside Deck Corners

Input Driveline Cat. 3 CV

Deck Driveline Cat. 2 w/ or w/o slip-clutch

Mowing capacity @2mph 2.68 acres

@4mph 5.37 acres

@6mph 8.1 acres

Flex-Wings 23° L-R, 22° F-B

Flex Center 13° F-B

* See dealer for complete warranty information.

Color Options:











www.landpride.com