



Disc scrapers are available to reduce build-up on discs.



Heavy-duty 1/2" thick bearing hangers resist the high torque from two 5/8" U-bolts.



Not all Disc Harrows are created equal. Signs of Top Quality from Land Pride:

- Tubular frame instead of angle iron
- Self aligning, sealed ball bearings
- Thick plate steel bearing hangers
- Bearing hangers with 2 U-bolts
- Front and rear leveling
- Optional furrow fillers, disc scrapers, center sweep, SMV Kit, and Tongue Jack

DH25 Series

**40-100 HP
DH2572, DH2596
Cat. 1 & 2**

Working Width (cm)	72" (183), 96" (244)
Weight - lb (kg)	947 (430), 1143 (518)
Disc Blade Size	20" or 22" Diameter
No. of Disc Blades	20, 24
Disc Blade Spacing	7-1/2"
Bearing Hanger	1/2" Plate, 2 each 5/8" U-bolts
Bearing Type - 2 per gang	Self aligning, sealed bearings
Angling	0, 7, 14, 21 Degrees w/angling adjustment handle
Frame Tubes	3" Square
Gang Tubes	4" x 3"
Gang Axle	1-1/8" Square, high carbon steel
Weight per Disc - lb (kg)	47 (21), 48 (22)
Center Sweep Option	9" Sweep
Disc Scrapers	Optional, Adjustable

Color Options:



DH35 Series

**45-100 HP
DH3510, DH3512
Cat. 1 Pull-type Hitch with Clevis**

Cutting Width	10', 12'
Weight - lb (kg)	2433 (1104), 2433 (1104)
Disc Blade Size	20" or 22" Diameter
No. of Disc Blades	24, 32
Disc Blade Spacing	7-1/2" or 9"
Bearing Hanger	5/8" Plate, 2 each 5/8" U-bolts
Bearing Type - 2 per gang	Self aligning, sealed bearings
Angling	Front: 0, 15, 18, 21 degrees; Rear: 0, 12, 15, 18 degrees
Frame Tubes	3" x 5"
Gang Tubes	3" x 5" x 1/4" wall tubing
Gang Axle	1" Square, high carbon steel
Weight per Disc - lb (kg)	DH3510: 79-84 (36-38) 7.5" spacing DH3512: 76-82 (34-37)
Weight per Disc (kg)	DH3510: 87-93 (39-42) 9" spacing DH3512: 81-86 (37-39)
Transport Tires	2 Std. 9.5Lx15, 4 Optional
Center Sweep Option	9" Sweep
Disc Scrapers	Optional, Adjustable

Color Options:

