

## Disc Harrows

### DH10 Series

Features	Benefits
Working widths	48", 60"
Cat. 1 3-point hitch	Fits Land Pride Quick-Hitch for easy one-person attachment and removal.
Weight	48" - 412 lbs.; 60" - 533 lbs. Heavy construction helps penetrate ground.
2" Square frame tube	Frame tubing is stronger than angle iron.
4 Adjustable gang angles	Cutting aggressiveness can be adjusted on the front and rear up to 21 degrees.
3" x 1 1/2" Gang tube, 1" Sq. gang axles, high carbon steel	High carbon square axles offer great strength in punishing conditions.
16" or 18" Notched or smooth disc blades	Choose notched blades for more aggressive digging and cutting action, or the smooth blades for light tilling. (16" blades only on 48" width)
3/8" Thick bearing hangers	Heavy-duty hangers resist the high torque from U-bolts and/or keep the discs out of the ground.
3/8" Frame side plates	Offer additional strength and reinforcement to the gang tube.
Self aligning sealed bearings	Self-aligning bearings offer long life while pounding through hard ground.

### DH15 Series

Features	Benefits
Working widths	60", 72" & 90"
Cat. 1 3-point hitch	Fits Land Pride Quick-Hitch for easy one-person attachment and removal.
Weight	60" - 629 lbs.; 72" - 714 lbs.; 90" - 865 lbs. Heavy construction helps penetrate ground.
2 1/2" Square frame tube	Frame tubing is stronger than angle iron.
4 Adjustable front gang angles 3 Adjustable rear gang angles	Cutting aggressiveness can be adjusted on the front and rear up to 21 degrees.
Adjustable gang handles	Easy adjustment of gang angles.
3" x 2" Gang tube, 1" Square gang axles, high carbon steel	High carbon square axles offer great strength in punishing conditions.
18" Notched or smooth disc blades	Choose notched blades for more aggressive digging and cutting action, or the smooth blades for light tilling.
3/8" Thick bearing hangers with two 5/8" U-bolts	Heavy-duty hangers resist the high torque from U-bolts and/or keep the discs out of the ground.
1/2" Frame side plates	Offer additional strength and reinforcement to the gang tube.
Self aligning sealed bearings	Self-aligning bearings offer long life while pounding through hard ground.
Optional scrapers	Scrapers will clean the discs off which can plug up and/or keep the discs out of the ground.

*Designs, specifications, features and information are subject to change without notice.*

## Features and Benefits

### Disc Harrows

#### DH25 Series

Features	Benefits
Working widths	72", 96"
Cat. 1 & 2 3-point hitch	Fits a wide variety of tractors.
Quick-Hitch compatible	Fits Land Prides Quick-Hitch for easy one-person attachment and removal.
Weight	72" = 947 lbs.; 96" = 1143 lbs. Heavy construction helps penetrate ground
3" Square frame tube	Heavy frame can handle 100 HP tractors.
Ball bearings	Self-aligning, sealed ball bearings.
4 Adjustable front gang angles 3 Adjustable rear gang angles	Vary the degree of aggressiveness on both front and rear gangs up to 21 degrees.
Gang adjustment handle	Easy adjustment of gang angles.
4" x 3" Gang tube	The gang tube resists twisting due to 4" horizontal width.
1 1/8" Square gang axles	Large axles can resist the high load put on them as the discs roll through the ground.
20" or 22" Notched disc blades	Larger discs will penetrate harder ground.
1/2" Thick bearing hangers	1/2" Thick bearing hangers resist high torque.
Optional scrapers	Scrapers will clean the disc blades off which can plug up and/or keep the discs out of the ground due to mud build-up. Adjustable.

*Designs, specifications, features and information are subject to change without notice.*