

## Features and Benefits

### Grooming Mowers, Rear Discharge

#### FDR16 Series

Features	Benefits
<b>3 Cutting widths</b>	48", 60", 72" Able to adapt to various size needs.
<b>Gearbox HP rating</b>	15 - 30 HP to cover a wide array of tractors.
<b>Rear discharge</b>	The wide, even dispersal of grass leaves a fine thin layer directly behind the mower, vs. a possible windrow to the side. Keeps grass from blowing in unwanted areas. Easier to mow around objects.
<b>Deflectors</b>	Built-in to throw material down, as well as forcing thrown objects down.
<b>Clevis type lower hitch points</b>	Allows for easy hook-up by being able to remove pins and back into clevises.
<b>Floating 3-point</b>	Top and bottom hitch points float up and down which allows the mower to float over uneven terrain.
<b>Roll formed front on deck.</b>	3/16" roll formed front deck edging for greater strength and impact resistance.
<b>Frame-over-deck design</b>	Frames takes stress out of deck by supporting it.
<b>3/16" Deck thickness</b>	Heavy deck material to aid in overall strength and longevity. Reinforced spindle mounts.
<b>Lower hitch points adjust in and out</b>	Accommodates many tractor configurations by adjusting in and out.
<b>Hard rubber tires</b>	Hard rubber tires are sandwiched between the rim halves, bolted in and can't go flat. Roller bearings allow for a long life.
<b>Heavy-duty Gauge wheel arms</b>	1/4" Gauge wheel arms increases strength.
<b>Non-aligned gauge wheels</b>	Rear wheels don't track behind the front wheels to reduce laying grass over.
<b>High Blade Tip Speed</b>	48" = 16,203 fpm 60" = 18,195 fpm      For cleaner cutting and better dispersion of clippings. 72" = 18,130 fpm
<b>Choices of Blades</b>	Low, medium, high-lift, or mulching blades are available to match customer needs and specific applications.
<b>Blade overlap</b>	1" blade overlap assures no skipping in tight turns.
<b>Heavy-duty roller bearings &amp; 1 3/8" machined spindles</b>	Roller bearings for smooth running and quiet operation, 1 3/8" machined spindles for durability, balanced performance, and accuracy. Cast iron housings for added protection and durability.
<b>Top greasing spindles</b>	Assures top bearing gets grease. No shields to remove.
<b>Single B-section Kevlar belt</b>	Simple one belt design. Kevlar material adds additional strength.
<b>Vacuum formed ABS belt guards</b>	No scratching, no rattling.
<b>Spring loaded adjustable idler</b>	Allows for constant and proper tension on belt. Better than adjusting gearbox for belt tension.
<b>Top Hitch</b>	Top hitch has two hook-up points which allows greater lifting leverage for smaller tractors.
<b>5 Year Limited Gear Box warranty</b>	Shows our confidence in the gearbox integrity. 5 year Parts & Labor with S/N 329841+.
<b>Driveline hanger</b>	For ease in hookup and storage of driveline. Keeps driveline off ground.
<b>Quick Hitch Compatible</b>	Compatible with Land Pride Quick Hitch for easy attachment and removal increases productivity. (Except 48")

*Designs, specifications, features and information are subject to change without notice.*