

Built for tough jobs and long days.

Discharging grass out the rear of the mower leaves a clean cut. It discharges grass evenly over a wide surface, and it doesn't discharge into unwanted areas.

HORSE
15-50
POWER



Solid rubber tires on 72" model are sandwiched between the rim halves and bolted in.



Main drive cast iron pulley offers superior strength and belt slippage control.



Some tractor and tire combinations do not allow enough room for the mower hook-up. Longer lower hitch clevises are available to easily correct this situation.



The all welded steel chassis forms a single integrated unit designed to support the mowing deck and to absorb shock loads incurred by the wheels and the front of the deck.



Blade spindles and bearings are precision fit in a cast iron housing.

FDR25 Series

15-50 HP

FDR2572, FDR2584

Cat. 1

Working Width (cm)	72" (183), 84" (213)
Overall Width (cm)	77" (196), 89" (226)
Weight - lb (kg)	718 (326), 812 (368)
Mowing Height	3/4" - 5-1/4"
Deck Material Thickness	3/16"
Blades 3 ea.	72: 1/4" x 2-1/2" x 25"
Heat Treated Alloy Steel	84: 5/16" x 2-1/2" x 29"
Blade Overlap	1-1/4"
Blade Spindles	Greaseable
Blade Tip Speed	18,130 FPM; 17,210 FPM
Gauge Wheels, 4-each	72": 3-1/4" x 10" solid rubber tire
	84": 4" x 11" semi-solid
Wheel Spindle	1" diameter
Drive Train	540 RPM B-Section V-Belt
Driveline	Heavy-duty w/quick coupler
Front Roller	Optional

* See dealer for complete warranty information.

Color Options:



- Lower hitch clevises adjust in and out for greater leverage
- Floating 3-point for superior ground hugging capabilities
- 1" Wheel spindles with nylon bushings for smooth casting
- Single B-section Kevlar belt, spring-loaded for maximum performance
- Rounded front corner without lip helps protect trees and fences
- Grease bearings from top without removing belt covers



www.landpride.com