

### *Landscape Rakes*

#### **LR15 Series**

<b>Features</b>	<b>Benefits</b>
<b>60", 72", 84", 96" working widths</b>	Meets a wide range of customer needs.
<b>20-35 Tractor HP Range</b>	Fits many tractors with a Cat. I 3-point hitch.
<b>Quick-Hitch adaptable</b>	Fits Land Pride Quick-Hitch for a quick and easy one person hook-up.
<b>Retractable Parking Stand</b>	Keeps the frame off the ground and makes hook-up easier.
<b>3 1/2" Pivot tube</b>	Heavy frame tube. Heaviest in its class.
<b>Rake teeth support channel</b>	Design with channel support. This design supports the rake teeth better than competitor models. Eliminates premature bending and teeth breakage.
<b>16 1/2" Rake height</b>	Can move a great deal of material.
<b>High carbon spring steel</b>	Allows teeth to keep their shape.
<b>Individual Replaceable teeth</b>	Makes replacing a damaged tooth quick and easy without removing all of the teeth.
<b>Angle 7 forward positions and 5 reverse positions</b>	Versatility in operation. Vary how much material to move.
<b>Dual gauge wheels</b>	Gives operator better depth control. Wide & Narrow wheels available.
<b>Flip-down grader blade with end plates (optional)</b>	Enables the rake to perform light blading duties for moving and leveling dirt as well as other materials. Grader blade can be flipped up when not in use.