

Ideal for ditching, road grading & all-around farm use.

RB25 Series

25-60 HP

RB2572, RB2584, RB2596

Cat. 1

Blade Width (cm)	72" (183), 84" (213), 96" (244)
Approx. Weight - lb (kg)	369 (167), 396 (180), 425 (193)
Angling	9 Fwd. Up to 45° 5 Rev. Up to 60°
Moldboard Height (mm)	17 1/2" (444)
Moldboard Thickness (mm)	5/16" (7.93)
Cutting Edge (mm)	1/2" x 6" (12.7 x 152.4) Reversible & Double Bevel Heat Treated
Options	Side Plates, Skid Shoes Gauge Wheel

Color Options:



- Parking stand
- Second top link hole for additional lifting leverage

RB35 Series

35-80 HP

RB3584, RB3596

Cat. 1 or 2

Blade Width (cm)	84" (213), 96" (244)
Approx. Weight - lb (kg)	533 (242), 566 (257)
Angling	9 Fwd. Up to 45° 5 Rev. Up to 30°
Tilt	5 Positions Up to 30° Right or Left
Offset (cm)	12" left or right
Moldboard Height (mm)	17 1/2" (444)
Moldboard Thickness (mm)	5/16" (7.93)
Cutting Edge (mm)	1/2" x 6" (12.7 x 152.4) Reversible & Double Bevel Heat Treated
Options	Side Plates, Skid Shoes, Gauge Wheel, Hydraulic Offset Cylinder

Color Options:



- Parking stand



The 2" x 2" x 3/8" angle iron reinforcement and formed top lip provide the moldboard with additional strength.



The heavy-duty turntable housing fits snug to keep wear to a minimum and to extend the life of the threaded shaft.