

Overseeders

OS15 Series

Features	Benefits
2" or 3" Spacing	Knife spacing for different geographic soil types, conditions and moisture.
Seed to soil contact	Knives create a slit, the seed is precisely placed in the slit and the roller incorporates seed to soil contact (for better seed germination).
Easy seed cup and seed box emptying	Flute is designed to allow easy clean out of material in seed box and seed flutes.
Seed box agitator	Eliminates seed bridging.
Seed cups with powder metal flutes	Superior metering accuracy by each flute. Powder metal dissipates heat to keep cups running cool.
Gauge wheel or rear roller seed cup drive	Gauge wheels keeps knives in ground more consistently in undulating terrain. Rear roller drive allows for closer seeding to obstructions.
Water tight seed box	Keeps water out and seeds in.
Wind guarded seed drop	Seed rate is consistent across width of the machine and is not hampered by windy conditions.
Straight Knives	More aggressive, picks up thatch.
Curved Knives	Less aggressive and less disturbance of thatch layer.
Small seeds box	Simultaneously seeds second type of seed.
Slit seeder attachment	Guides seed directly into slit. Good for overseeding expensive grasses to insure good seed to soil contact.
Front roller (Option)	Used to set seeding depth with units equipped with rear roller drive. Precise depth control.
Working widths	48", 72"
HP rating	25-60 HP
Offset hitch – 48" unit	Offset by 10" to cover right tire track.
Fits Land Pride Quick-Hitch	Aids in one person hook-up.
Machine weights	48" - 1260 lbs; 72" - 1605 lbs.
0"-1 1/2" Depth adjustment	Adjust depth for different seed types, soil conditions and moisture.
High carbon heat-treated knives	Last longer in sandy soils.
High tensile roller chain	Provides a smooth and quiet drive.
1 Bushel per foot seedbox	Fill less often with a large box.
Seed splash guard	Seedbox lid has a guard to prevent seed from being spilled between lid and box.
Heavy-duty lid	Lid won't buckle or slam shut in high winds.
Lift hooks	Allow for easy loading & unloading from trailers
Packer wheel scraper	Prevents soil buildup on packer wheels in moist conditions.
Covered drive chains	Drive chains are covered for safety, as well as keeping tree branches away to eliminate chain jumping.
Warranty	5 Years on gearbox. One year parts & labor.

Designs, specifications, features and information are subject to change without notice.