

51

## **Powered Rakes**

## PR16 Series (3-Point)

Features	Benefits
Working widths	60", 72" & 90"
Tractor Horsepower Range	PR1660 = 25 - 40 HP PR1672 = 25 - 40 HP PR1690 = 35 - 75 HP
Cat. 3 drivelines with slip-clutch on second driveline	Slip-clutch offers protection to the gearbox and entire power train when a tough obstruction is encountered with the roller.
6" x 3" x 1/4" Tube Frames	Superior in strength.
3/4" x 1 1/2" Carbide Tipped Studs	Carbide tipped studs are very tough, used in the mining industry, this offers a long life to the studs. Studs can be replaced one at a time.
15 Degrees left or right angling	By angling either direction, the user has many options on what direction to work his area.
Gauge wheels with sealant	Easy to adjust vertically to set working depth. Has tall and wide tires that keep turning in fluffy soil. Sealant helps seal against punctures.
End plates with storage	End plates can be used to hold dirt to aid in filling low spots. Easily store the end plates on the Powered Rake so that they are always with the Rake when needed.
Material control deflector	Material control deflector is used to determine what size of material to let pass through the roller and what size to move out.
#50 Double continuous roller chain	Double roller chain can take the fluctuation loads from the roller due to varying ground conditions.
Cast Iron chain guard housing	Strong enough to protect chain in harsh conditions.
Drive chain enclosed in oil bath with drain plug	Oil keeps the chain and sprockets lubricated to keep abrasion to a minimum. Easy to maintain and change oil level.
Replaceable skid shoes	Skid shoes protect larger and vital parts of the unit. As they wear due to soil contact, they can easily be replaced.
5 Year gearbox warranty	Shows our confidence in the gearbox integrity.
Quick Hitch	Can be used with Land Pride Quick-Hitch. (May need extra driveline.)