

Blades, Rear

RBT55120 Model

| Features | Benefits |
|--|--|
| Warranty | One year parts and labor. See warranty page for complete details. |
| 120" Working width | Can handle large capacities. |
| 90-180 HP Range | Fits a wide variety of tractors. |
| Cat. 2 and 3 | Bushing provided to go from Cat. 2 to Cat. 3 enables a wider variety of tractors to be used. |
| Quick hitch compatible | Compatible with Land Pride Quick hitch for easy attachment and removal. Increases productivity. |
| Blade angles left or right up to 45° in either direction | (15 positions manually: Center, 7 clockwise and 7 counterclockwise) (Hydraulically: Any degree up to 45 degrees) Allows operator to set the blade at the angle of his choice up to 45° to move the desired amount of material with satisfactory results. |
| Blade offsets left or right up to 33" | (15 positions manually: Center, 7 positions left and 7 positions right) (Hydraulically: Any position up to 33") Allows the operator to position the end of the moldboard beyond tractor tire and close to solid obstacles such as fences, buildings and abutments. |
| Blade tilts up or down up to 15° | Allows the operator to do simple tasks such as putting a crown in the middle of a road to making V-type ditches of various sizes. |
| Fully welded reinforced main frame | Overall mainframe strength is enhanced due to being fully welded. |
| Heavy-duty pivot assembly with 4" solid steel kingpin | 1" Plate steel turntable and 4" kingpin for handling the high amount of torque that can be transferred to this area. |
| Formed 19" moldboard with top lip reinforcement | Formed moldboard with 90 degree bent top for additional strength. Tall moldboard allows for a great deal of material to be moved. |
| 5/16" Moldboard with 1/4" reinforcement | Heavy-duty moldboard to handle loads from 180 HP tractors. |
| Heavy-duty pivot assembly | 1" Plate steel turntable and 4" kingpin handle tremendous torque delivered by up to 180 HP tractors. |
| Grease points in front pivot shaft | Helps front pivot shaft to easily move. |
| Reversible cutting edge | Lengthens blade life by being able to turn cutting edge over and use other edge. |
| Retractable parking stand | Enables one person hook-up and keeps the mainframe off of the ground. |
| Skid shoes (Optional) | Skid shoes protect moldboard from hitting low lying obstructions such as manhole covers. |
| End plates (optional) | End plates allow the blade to hold material in to drag from one spot to another. |
| Hardened wear edges (optional) | Attach to outer edges of moldboard to prevent to wear in moldboard during ditching. |
| Single or dual gauge wheels (optional) | Gauge wheels position the height of the blade to aid in grading. |

Designs, specifications, features and information are subject to change without notice.