

Blades, Rear

RBT60 Series

Features	Benefits
Warranty	One year parts and labor. See warranty page for complete details.
10 ft. & 12 ft. Working widths	Choice of two sizes to pick from. Both sizes handle large capacities.
High HP Range 2-Wheel Drive 4-Wheel Drive	225 Hp with 10 ft. blade & 175 HP with 12 ft. blade 200 Hp with 10 ft. blade & 160 HP with 12 ft. blade
Cat. II and Cat III 3-Point Hitch	Can go from Cat. II to Cat. III 3-point tractor. Enables a wider variety of tractors to be used.
Quick hitch compatible	Compatible with Land Pride QH20 Cat. II Quick hitch for easy attachment and removal. Increases productivity.
Blade angles left and right up to 45 degrees hydraulically	Allows the operator to set the blade at the angle of his choice to complete the job with satisfactory results.
Blade offsets left and right up to 55" hydraulically	Allows the operator to position the end of the moldboard beyond tractor tire and close to solid obstacles such as fences, buildings and abutments.
Blade tilts up and down up to 15 degrees hydraulically	Allows the operator to do simple tasks such as putting a crown in the middle of a road to making V-type ditches of various sizes.
Mainframe is fully welded and reinforced	Overall Mainframe strength is enhanced due to being fully welded.
Heavy-duty pivot assembly with 4 1/2" Diameter solid steel moldboard kingpin	1" Plate steel turntable and 4 1/2" King pin for handling high torque in this area up to 225 HP 2-wheel or 200 HP 4-wheel drive tractors with 10 ft. moldboard and 175 HP 2-wheel or 160 HP 4-wheel drive tractors with 12 ft. moldboard.
Formed 19" high moldboard	Can move a great deal of material in a short time.
1/2" Formed Moldboard with 3/8" formed channel reinforcement	Makes it one of the strongest moldboards in its class for handling heavy loads.
Retractable parking stand	Enables one person hook-up and keeps the mainframe off of the ground.
Front pivot shaft has two grease points	Helps front pivot shaft to move easily.
Heavy-duty blade pivot assembly	1" Plate steel turntable and 4 1/2" kingpin handle tremendous torque delivered by up to 225 HP tractors.
Accessories	
Skid shoes	Skid shoes protect moldboard from hitting low lying obstructions such as manhole covers.
End plates	End plates allow the blade to hold material in to drag from one spot to another.
Dual gauge wheels	Gauge wheels position the height of the blade to aid in grading.