36 SERIES ROTARY CUTTER

2-1/2" CUTTING CAPACITY

2-1/2"

Give your pasture that well-groomed look!

Deck Rings Now Available!





The 1" thick, 4" wide reinforcement aids the dishpan in withstanding the constant punishment the overall drivetrain must endure.

The heavy-duty turnbuckle keeps the center and wing axles at the same cutting height. With grease fittings incorporated in the turnbuckle, free motion is maintained for





RC36 Series

MEDIUM DUTY

50-160 HP RC3615

Working Width (cm) 15' (457)

Overall Width 15' 8"

Min Transport Width 8

Overall Length 15' 1"

Machine Weight - Ib (kg) 3,730 (1692)

Tongue Weight - lb 1,240

Cutting Height 2" - 14"
Cutting Capacity 2-1/2"

Height Adjustment 3" x 8" Cylinder, Hose, Fittings &

Stroke Control Spacers

Hitch Standard Clevis, Swivel, Pintle or

Bar-Tite Hitch

Deck Thickness 10 Gauge

Deck Height 9"

Deck Shock Protection Spring Cushioned Center Axle

Deck Rings Optional

Side Thickness 1/4"

Safety Guards Front & Rear: Single or Double

(must choose) Chain or Rubber

Skid Shoes Wings and Center, Replaceable

Blades 1/2" x 4" Heat Treated Free **(2 per section)** Swinging Alloy Steel w/Uplift

Blade Overlap 6

Blade Tip Speed 540 RPM: 15,268 fpm on center,

(Feet per minute) 15,000 fpm on wings

1000 RPM: 15,578 fpm on center, 14,620 fpm on wings

Dishpan 3/16" Round, Dish shaped

with 1" x 4" blade bar

Hydraulics Wings: 2-1/2" x 12" Cylinder,

Hoses & Fittings

Gearbox 540 or 1000 RPM: 160 HP Divider,

110 HP Center & Wings

Gearbox Output Shaft 2"

Gearbox Input Shaft 1-3/4" 20 Spline

Input Driveline Constant Velocity U-Joint;

540 & 1000 RPM: CAT. 5

Connecting Drivelines Cat. 4 with Slip-clutch

Maximum Turning Angle 80° with Constant Velocity U-Joint

Tires - 4 or 6 Laminated, Aircraft w/wo Foam**

- * See dealer for complete warranty information.
- ** See dealer for sizes.

Color Options:









- 1" Solid and continuous hinge rods provide superior support from section to section
- · Smooth top for easy clean off