

Rotary Cutters, Folding Deck

RC3615 and RCM3615 Models

Features	Benefits
Surpassed rugged industry standards	All Land Pride Rotary Cutters have been designed and tested and meet rigorous voluntary testing procedures.
Factory assembled	Arrives for quick and easy set-up. Minimal time is wasted setting or prepping the unit.
5 Year gearbox warranty	Shows confidence in gearbox integrity.
160 HP Divider gearbox and 110 HP wing gearboxes	A rugged heavy built gearboxes capable of handling heavy cutting applications.
Gearbox seal protection	Gearbox bottom seal protection for longer bearing life.
Smooth Top Design	Allows for easy cleaning of deck.
Low tongue weight	Ideal for smaller HP tractors by reducing the amount of weight on the drawbar.
Narrow tongue construction	Allows for a tighter turning radius.
Input Driveline: Cat. 5 CV	Driveline is matched just right for capacity of tractor. Constant velocity (CV) U-joint allows for 80 degree turns without doing damage to the driveline.
Cat. 5 intermediate & Cat. 4 wing drivelines with slip-clutches	Driveline is sized right for the intended cutting capacity. Slip-clutch will slip under load instead of twisting the driveline.
Slip-clutch drivelines	Slip-clutches are designed to slip to minimize twist damage to the driveline profiles.
High Blade tip speed 15,000 FPM Wing RC3615 15,268 FPM Center RC3615 14,620 FPM Wing RCM3615 15,578 FPM Center RCM3615	Allows clean cutting of material.
6" Blade overlap	Eliminates skipping during turns.
Left wing rotates clockwise	Better discharge of material. Picks up tractor tracks.
3/16" Round stump jumper	Standard thick stump jumper material keeps damage to a minimum.
1/4" Sidewall thickness	Increased thickness reduces damage from objects being thrown into deck sidewalls.
Self-leveling hitch	Reduces drawbar wear by keeping hitch level while going through ditches.
Hinged wing sections	Allows cutter to follow terrain. Ideal for rough ground where hillsides, ditches and hollows can cause uneven cutting.
1" Solid hinge rods	Larger diameter hinge rod gives greater strength to the cutter from front to rear, and in the hinge area itself.
Wing transport locks	Wing transport locks securely hold the wings in the folded position in case of hydraulic failure.
Enclosed front to rear dual leveling rods	Dual leveling rods enable the cutter to pull equally on the rear axle during travel over rough terrain.
5-Bolt hubs	5-Bolt hubs makes the wheel assembly more durable and longer lasting.
Spring cushioned center-axle	Protects unit from bumps and ground shock.
Replaceable wheel spindles	Wheel spindles can be replaced when damaged without replacing entire axle assembly.
Wheel options	Laminated tires: Eliminates flats. Airplane tires without foam filling: Give better cushion while transporting. Airplane tires with foam filling: Give better cushion while transporting and can't go flat.
Double swivel hitch option	Great for uneven terrain, reduces drawbar wear. Hitch pivots freely up and down and pivots about the tractor drawbar.
Bar-tite hitch option	Ideal for extreme conditions. Clamps tight to drawbar eliminating drawbar wear.

Designs, specifications, features and information are subject to change without notice.