

50 SERIES ROTARY CUTTER

20' Folding

3"
CUTTING
CAPACITY

Put a great deal of work behind you in a hurry.

Roadsides, pastures, set-aside acres and crop residue are perfect jobs for the 20' Commander. Wing decks float independently, and follow the contour of the land leaving a nicely cut surface.



The 20' cutting width, 2" to 14" cutting height and ability to cut weeds and brush up to 3" in diameter make the RC5020 well suited for varied applications. Various safety guard choices make these an excellent choice for state and municipal mowing applications.

Outer wing wheels can be single or dual. Duals are ideal when mowing in areas where one wing needs to flex uphill. The outer wheel rides up the embankment and keeps the deck from gouging. Wheel spindles are bolt-in to allow easy change out.



Commander

RC50 Series

HEAVY DUTY

70-250 HP

RC5020

Pull-Type

| | |
|-----------------------------------|--|
| Working Width (cm) | 20' (607) |
| Overall Width | 20' 9-1/2" |
| Min. Transport Width | 8' 9" |
| Overall Length | 19' 3" with Laminated Tires |
| Machine Weight - lb (kg) | 6,528 (2961) |
| Cutting Height | 2" - 14" |
| Cutting Capacity | 3" Diameter |
| Hitch | Standard Clevis, Swivel, Pintle or Bar-Tite Hitch |
| Tongue Weight - lb | 2,300 |
| Maximum Turning Angle | 80° with Constant Velocity U-Joint |
| Deck Thickness | 3/16" |
| Deck Height | 10-1/2" |
| Deck Shock Protection | Spring Cushioned Axle |
| Deck Rings | Optional |
| Side Thickness | 1/4" |
| Safety Guards (must choose) | Front and Rear: Single or Double Chain or Rubber |
| Skid Shoes | 1 each wing, 2 on center section, replaceable |
| Blades | 1/2" x 4" High Lift |
| Blade Tip Speed (Feet per minute) | 540 RPM: 17,377 fpm on center, 17,329 fpm on wings 1000 RPM: 18,165 fpm on center, 18,317 fpm on wings |
| Blade Overlap | 6" |
| Dishpan | 3/16" Round, Dish shaped w/ 1" steel plate support |
| Baffle Kit | Optional - Rear |
| Hydraulics | Wings: 3-1/2" x 12" Cylinder, Hoses and Fittings Axle: 4" x 8" Cylinder, Hoses, Fittings and Stroke Control Spacers |
| Gearbox | 540 RPM or 1000 RPM: 250 HP Divider, 210 HP Center & Wings |
| Gearbox Output Shaft | 2-3/8" |
| Gearbox Input Shaft | 1-3/4" 20 spline |
| Input Driveline | Cat. 5 |
| Connecting Drivelines | 4-Plate Slip Clutch; Cat. 5 |
| Tires 6 or 8 | Laminated, Aircraft w/wo Foam** |

* See dealer for complete warranty information.

** See dealer for sizes.

Color Options:



7 YEAR
Limited Gearbox
Warranty