

Rotary Cutters, Single Deck

RCD1884 Model

Features	Benefits
Surpassed rugged industry standards	All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
5 Year gearbox warranty	Shows our confidence in the gearbox integrity.
Gearbox Seal Protection	Gearbox bottom seal protection for longer bearing life.
Cat. 3 main driveline with 2-plate slip-clutch	2-Plate slip-clutch protect driveline and gearboxes. slip-clutch is more convenient than shear bolt for continual work.
Shock absorbing flex-coupler between main and side gearboxes	Protects intermediate drive shaft and side gearbox from hard objects in the blade path.
10" Deck offset to the right	Allows the operator to cut closer to bodies of water, drainage ditches, roadways and objects such as fence lines, guard rails, buildings and trees.
Lower clevis type 3-point hitch	Allows for ease of hook-up to tractor. Also adds additional strength allowing for an even pull from the tractor's lower arms, vs. pulling on a single pin design.
Fully welded 10 gauge deck	Fully welded deck adds additional strength to the deck. 10 Gauge decks can withstand more abuse than decks with lighter gauge.
Box tubing deck supports	Makes for a stronger rigid deck.
Round back design	Helps discharge grass better than enclosed or partially enclosed cutters.
11 5/8" Deck Height	Allows cutter to handle heavy cutting conditions.
1 1/2" to 12" Cutting height	Provides for a wide range of cutting conditions.
Skid shoes	Provides sidewall reinforcement and protection to bottom of sidewall.
1/2" x 4" Heat-treated free swinging blades	Free swinging protects from obstructions. Heat-treated offers longer life.
1/2" x 4" Blade bar	Heavy-duty blade bar adds support to stump jumper and gearbox output shaft.
Splined blade bar hub	Allows for tight positive fit of stump jumper and blade bar to gearbox output shaft.
Stump jumper	Standard round stump jumper slides over stumps, rocks and debris.
Front and rear guarding	Protect against flying debris. Optional front rubber or single chain guarding. Standard rear metal band or optional rear extended metal guarding.
Optional 15" Laminated tailwheel 4" x 16" Molded rubber	Laminated material is long lasting in rough conditions and can't go flat. Can't go flat.