

## Rotary Cutters, Single Deck

### RCF3096 & RCF(M)3010 Models

Features	Benefits
<b>Surpassed rugged industry standards</b>	All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures.
<b>540 or 1000 RPM</b>	Fits wider variety of tractors.
<b>High Gearbox HP rating</b>	Gearboxes are built rugged. See Specifications for actual Gearbox HP ratings.
<b>5 Yr. limited gearbox warranty</b>	Shows our confidence in the gearbox integrity.
<b>3 Gearboxes</b>	Allows equal torque to be spread to left and right gearbox.
<b>Splined rubber flex-couplers between the center and outboard gearboxes</b>	Protects the driveline and gearboxes from hard objects in the blade path.
<b>Pull-Type constant velocity driveline Option</b>	Constant velocity driveline reduces chatter and extends life of U-joint during turns.
<b>Slip-clutch protection on main driveline</b>	Slip-clutch is more convenient than shear-bolt, protects gearbox against sudden impact.
<b>8'- Cat. 1 &amp; 2 or 10'- Cat. 2 &amp; 3 3-Point &amp; Semi-mount Hitches or Pull-type Hitch</b>	Fits a wide range of tractors. Semi-mount and Pull-type fit older tractors without a top link and smaller tractors without enough lift capacity.
<b>10 Gauge deck, fully welded</b>	Fully welded deck adds rigidity.
<b>1/4" Thick sidewalls</b>	Protects sidewalls from thrown objects.
<b>Round back design</b>	Allows for cleaner and efficient discharge of material, helps eliminate damage to rear corners by not sticking out.
<b>Pull-type w/dual leveling rods</b>	Dual leveling rods eliminate deck twisting when going over uneven terrain.
<b>Chain or rubber guard option</b>	Reduces flying debris.
<b>Full length skids with replaceable shoes</b>	Adds reinforcement to side panels. Replaceable shoes allow for change before wearing through to weld-on piece.
<b>Splined blade hub</b>	Splined blade hub offers tight non-slipping attachment to output shaft.
<b>3/16" Round stump jumper</b>	Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft.
<b>1" x 4" Blade bar</b>	Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft.
<b>1/2" x 4" Heat-treated blades</b>	Heat-treated blades last longer than non-heat-treated blades.
<b>2 1/2" Diameter cutting capacity</b>	Aids in cutting brush.
<b>High blade tip speed</b>	Means cleaner cutting. See Specifications for actual blade tip speeds.
<b>Laminated tires</b>	Laminated tires can handle almost any condition and don't go flat.
<b>Quick-Hitch adaptable</b>	3-point and semi-mount are Quick-hitch adaptable.
<b>Paint Options</b>	Choice of red, orange, green, or tan to match popular tractor lines.

*Designs, specifications, features and information are subject to change without notice.*