

**Ideal for cleaning around the farm, the pond or empty lots in the city.**



10 Gauge dishpan with 1" thick blade bar slides over stumps, rocks and debris.



**2" CUTTING CAPACITY**

## RCR18 Series

60", 72": 20-65 HP

84": 45-90 HP

RCR1860, RCR1872, RCR1884

Cat. 1

<b>Working Width (cm)</b>	57" (145), 69" (173), 84" (213)
<b>Overall Width</b>	62", 74", 89"
<b>Overall Length</b>	96", 108", 135"
<b>Weight* - lb (kg)</b>	609, 749, 851
<b>Cutting Height</b>	60: 1-1/2" - 13" 72: 1-1/2" - 11-1/2" 84: 2" - 11"
<b>Cutting Capacity</b>	2" Diameter
<b>Deck Thickness</b>	10 Gauge
<b>Deck Height</b>	7-1/2", 9", 9-1/8"
<b>*Safety Guards</b>	Rubber or chain, Rear metal band is standard
<b>Skids</b>	1/4" x 2" Weld on
<b>Blades</b>	60/72: 1/2" x 3", 84: 1/2" x 4" Heat Treated Alloy Steel Free Swinging Blades
<b>Blade Tip Speed</b>	16,363 fpm, 14,853 fpm, 17,113 fpm
<b>Dishpan</b>	60/72: Round 10 Ga. x 24" Dia., Dish Shaped 84: Oval 10 Ga., Dish Shaped
<b>Gearbox</b>	540 RPM PTO Driven Gearbox Cast Iron Housing
<b>Driveline</b>	60/72: ASAE Cat. 3 84: Cat. 4 Standard - 1/2" Shear Bolt Protection Optional - Bolt 2 Plate Slip Clutch
<b>Tailwheel</b>	60/72: 4" x 16" Solid Rubber Tire 84: 4" x 8" x 15" Laminated Tire or Dual laminated optional Cast Iron Hub

\* See dealer for complete warranty information.

Color Options:



**5 YEAR**  
Limited Gearbox  
Warranty



- Floating 3-point allows deck to hug the terrain
- Fully welded deck adds additional strength
- High blade tip speed ensures clean cut
- Single or dual tailwheel on 84"
- Heavy-duty tailwheel spindle
- Rubber or chain guards protect against flying debris
- All-welded formed channels front to rear add superior strength
- Lower clevises for easy hookup