

DUAL SPINDLE

1-1/2"
CUTTING
CAPACITY

1-1/2"

A perfect fit for any size farm.

The RCR25 Series is just perfect for those medium sized chores. Designed for performance in pastures, set aside acres, roadsides and routine farm maintenance.

Pull-type — The Pull-type model features two leveling rods that connect the rear axle to the front tongue. This enables the deck to stay level during uneven ground conditions. The height controlling axle cylinder is attached to two deck springs which help cushion the cutter in rough terrain.

3-Point — The 3-point unit utilizes two castoring laminated tailwheels for smooth, trouble-free performance. The easy to attach clevis hitch is designed to fit Cat. 1 or 2 tractors on the 96" model, and Cat. 2 or 3 tractors on the 10' model.



Narrow tongue on pull-type allows for tight turns.

Front and rear guarding is highly recommended in any application. Please be sure you understand how your Rotary Cutter is equipped upon purchase. All Land Pride Rotary Cutters are tested and pass rigorous voluntary testing requirements as specified by ISO, ASAE and SAE.

RCR25 Series

Pull-Type: 8': 40 - 110 HP, 10': 50 - 110 HP

3-Point: 8': 50 - 110 HP, 10': 60 - 110 HP

RCR2596, RCR2510

3-Point Hitch 8': Cat. 1 & 2

10': Cat. 2 & 3

Working Width (cm)	7'10" (239), 9'10" (300)
Overall Width	8'2", 10'3"
Overall Length	Lift - 8'11", Pull - 11'3" Lift - 9'2", Pull - 12'1"
Weight - lb (kg)	Lift-Type 8': 1,380 (625) 10': 1,750 (793) Pull-Type 8': 1,665 (755) 10': 2,035 (923)
Deck Material Thickness	10 Gauge
Deck Height	9-5/8"
*Safety Guards (choose)	Front or Rear Chain / Front or Rear Rubber
Skids	Replaceable
Gearbox	540 rpm or 1000 rpm, Cast Iron Housing, Beveled Gears
Cutting Height	8': 2" - 12" 10': 2" - 10-1/2"
Cutting Capacity	1-1/2"
Blades	1/2" x 4" Heat Treated, Free-Swinging Suction Blades
Blade Tip Speed	8': 540 RPM: 14,592 fpm 10': 540 RPM: 17,749 fpm 1000 RPM: 18,035 fpm
Dishpan	3/16", Round, Dish Shaped
Driveline	540 rpm - 4 Plate Slip-Clutch 1000 rpm - 2 Plate Slip-Clutch
Tailwheel	Lift-Type: 2 each, 4" x 8" x 15-1/4" Laminated Pull-Type: 2 each, 6" x 9" x 21" Laminated or 24" Aircraft Tires

See dealer for complete warranty information.

Color Options:

