

## Features and Benefits

### Rotary Cutters, Single Deck, Dual Spindle

#### RCR25 Series

Features	Benefits
<b>Surpassed rugged industry standards</b>	All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
<b>Tractor HP range</b>	3-point (2596 Model = 50 - 110 HP) & (2510 Model = 60 - 110 HP) Pull-type (2596 Model = 30 - 110 HP) & (2510 Model = 50 - 110 HP)
<b>540 or 1000 RPM</b>	Fits wider variety of tractors. (RCR2596 is 540 RPM only)
<b>Gearbox HP rating</b>	120 Horsepower on splitter gearbox and 60 HP on outboard gearboxes.
<b>5 Year gearbox warranty</b>	Shows our confidence in the gearbox integrity.
<b>3 Gearboxes</b>	Allows equal torque to be spread to left and right gearbox.
<b>Splined rubber flex- couplers between the center and outboard gearboxes</b>	Protects the driveline and gearboxes from hard objects in the blade path.
<b>Constant Velocity U-Joint option on RCR2510 &amp; RCRM2510 Pull-type</b>	Reduces chatter and extends life of U-joint during turns.
<b>Slip-clutch protection on main driveline</b>	Slip-clutch is more convenient than shear-bolt, protects gearbox against sudden impact.
<b>3-Point or Pull-type</b>	Pull-type fits older tractors without a top link or smaller tractors without enough lift capacity. (RCR2596 3-point: Cat. 1 & 2) (RCR2510 & RCRM2510 3-point: Cat. 2 & 3)
<b>High productive cutting width</b>	RCR2596 cuts 8'-0" width. RCR2510 & RCRM2510 cuts 9'-10" width.
<b>Fully welded 10 Gauge deck</b>	Fully welded deck adds rigidity.
<b>3/16" Sidewall thickness</b>	Protects sidewalls from thrown objects.
<b>Obstacle free underside</b>	Underside of deck is free of reinforcement members which tend to allow material to lodge.
<b>Round back design</b>	Allows for cleaner and efficient discharge of material, helps eliminate damage to rear corners by not sticking out.
<b>Dual leveling rods on Pull-type</b>	Dual leveling rods eliminate deck twisting when going over uneven terrain.
<b>Chain or rubber shield option</b>	Reduces flying debris.
<b>Full length skids with replaceable shoes</b>	Adds reinforcement to side panels. Replaceable shoes allows for change before wearing through to weld-on piece.
<b>Splined blade hub</b>	Splined blade hub offers tight non-slipping attachment to output shaft.
<b>3/16" Round stump jumper</b>	Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft.
<b>1" x 4" Blade bar</b>	Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft.
<b>1/2" x 4" Heat-treated blades</b>	Heat-treated blades last longer than non-heat-treated blades.
<b>1 1/2" Dia. cutting capacity</b>	Aids in cutting brush.
<b>High Blade tip speed</b>	RCR2596 (540 rpm) = 14,792 fpm RCR2510 (540 rpm) = 17,749 fpm RCRM2510 (1000 rpm) = 18,035 fpm Means Cleaner Cutting of material.
<b>Laminated tires</b>	Laminated tires can handle almost any condition.
<b>Airplane tires (Pull-Type only)</b>	Airplane tires offer smooth roadability.
<b>Fits Land Pride Quick Hitch</b>	Allows for quick and easy one person hook-up.

*Designs, specifications, features and information are subject to change without notice.*