

ROTARY TILLERS



Spring-loaded rear deflector keeps tailgate on the ground to level and keeps larger debris in for more pulverizing action.

Ready to tackle the rough stuff.



Adjustable Lower Hitch

With a 76" working width, and adjustable lower hitch clevises, taking out your tire track is usually achievable. This allows for less overlap needed, meaning less time in the tractor seat.



* See dealer for complete warranty information.

RTA25 Series

25-55 HP

RTA2562, RTA2570

Cat. 1

Width-endplate to endplate (cm)	64" (162), 70" (178)
Overall width	68", 76"
Weight - lb (kg)	627 (284), 639 (290)
Number of Flanges	8, 9
No. of Blades per Flange	6 C-Shape
Blade Spacing	7-7/8"
Max. Tilling Depth	7"
Skid Shoe Settings	6
Rotor Swing Dia	17" (43)
Rotor Shaft Speed	220 rpm at 540 rpm PTO
PTO Driveline	ASAE Category 3 Heavy Duty Shear Bolt or Slip Clutch
Gearbox	55 HP, 540 rpm, Cast Iron Housing, Drain Plug
Drive Chain	#100 in Oil Bath
Sprockets	Splined Bores
Color Options:	 



RTA35 Series

35-75 HP

RTA3576

Cat. 1

Width-endplate to endplate (cm)	76" (193)
Overall width	81-1/2"
Weight - lb (kg)	856 (388)
Number of Flanges	8
Number of Blades per Flange	6 C-Shape
Blade Spacing	9"
Maximum Tilling Depth	7"
Skid Shoe Settings	6
Rotor Swing Diameter	19"
Rotor Shaft Speed	204 rpm at 540 rpm PTO
PTO Driveline	ASAE Category 4 Slip Clutch
Gearbox	75 HP 540 rpm, Cast Iron Housing, Drain Plug
Drive Chain	#100 in Oil Bath
Sprockets	Splined Bores

Tilling depth depends on conditions and fluffiness of tilled area.

Color Options:

