

ROTARY TILLERS



The 15 Series Land Pride Rotary Tiller is sized just right for compact tractors that are used on hobby farms and in nurseries in every corner of the country.



RTA15 & RTR15 Series

17-50 HP

RTA1550, RTA1558, RTA1566, RTA1574
RTR1550, RTR1558, RTR1566, RTR1574
Cat. 1

Width-endplate to endplate (cm)	50" (127), 58" (147) 66" (168), 74" (188)
Overall width	56-1/4", 64-1/4" 72-1/4", 80-1/4"
Weight - lb (kg)	455 (206), 489 (222) 523 (237), 557 (253)
Number of Flanges	6, 7
No. of Blades per Flange	4 C-Shape
Blade Spacing	7-7/8"
Max. Tilling Depth	6-1/2"
Skid Shoe Settings	7
Rotor Swing Diameter	15"
Rotor Shaft Speed	211 rpm at 540 rpm PTO
PTO Driveline	ASAE Category 3 Off-Center Shear Bolt or Slip Clutch
Gearbox	50 HP, 540 rpm, Cast Iron Housing, Drain Plug
Drive Chain	#80 in Oil Bath
Sprockets	Hardened Teeth, Splined Center

Color Options:



The sideshift feature on the 15 Series Rotary Tillers enables you to shift the tiller to the right to corner a tire track or get closer to obstacles, while allowing the driveline to remain straight.



www.landpride.com