

## We have traditional Forward Rotation . . .



## And the most popular Reverse Rotation . . .



\* See dealer for complete warranty information.

\*\* See page 47 for reverse-till diagram.

### RTA20 Series

23-50 HP

RTA2064, RTA2072

Cat. 1

|                                 |   |
|---------------------------------|---|
| Width-endplate to endplate (cm) | 64" (162), 72" (183)                                    |
| Overall width                   | 70-1/4", 77-5/16"                                       |
| Weight - lb (kg)                | 689 (313), 734 (333)                                    |
| Number of Flanges               | 8, 9  |
| No. of Blades per Flange        | 6 C-Shape   |
| Blade Spacing                   | 7-1/2"  |
| Max. Tilling Depth              | 7"  |
| Skid Shoe Settings              | 7   |
| Rotor Swing Diameter            | 17"   |
| Rotor Shaft Speed               | 220 rpm at 540 rpm PTO                                  |
| PTO Driveline                   | ASAE Category 3<br>Heavy Duty Shear Bolt or Slip Clutch |
| Gearbox                         | 50 HP, 540 rpm, Cast Iron Housing, Drain Plug           |
| Drive Chain                     | #80 in Oil Bath   |
| Sprockets                       | Splined Bores   |

Tilling depth depends on conditions and fluffiness of tilled area.

Color Options:



### RTR20 Series

23-50 HP

RTR2064, RTR2072

Cat. 1

|                                 |   |
|---------------------------------|---|
| Width-endplate to endplate (cm) | 64" (162), 72" (183)                                    |
| Overall width                   | 70-1/4", 77-5/16"                                       |
| Weight - lb (kg)                | 748 (339), 795 (361)                                    |
| Number of Flanges               | 8, 9  |
| No. of Blades per Flange        | 6 C-Shape   |
| Blade Spacing                   | 7-1/2"  |
| Max. Tilling Depth              | 7"  |
| Skid Shoe Settings              | 7   |
| Offset                          | 14", 18"  |
| Number of Sitting Tines         | 43, 48  |
| Rotor Swing Diameter            | 17" (43)  |
| Rotor Shaft Speed               | 220 rpm at 540 rpm PTO                                  |
| PTO Driveline                   | ASAE Category 3<br>Heavy Duty Shear Bolt or Slip Clutch |
| Gearbox                         | 50 HP, 540 rpm, Cast Iron Housing, Drain Plug           |
| Drive Chain                     | #80 in Oil Bath   |
| Sprockets                       | Splined Bores   |

Tilling depth depends on conditions and fluffiness of tilled area.

Color Options:

