

## RTR25 Series

**25-55 HP  
RTR2570  
Cat. 1**

<b>Width-Endplate to Endplate (cm)</b>	70" (178)
<b>Overall Width</b>	76" (193)
<b>Weight - lb (kg)</b>	868 (394)
<b>Number of Flanges</b>	9
<b>No. of Blades Per Flange</b>	6 C-Shape
<b>Blade Spacing</b>	7-7/8"
<b>Max. Tilling Depth</b>	7"
<b>Skid Shoe Settings</b>	7
<b>Offset</b>	Up to 5"
<b>Number of Sifting Tines</b>	42
<b>Rotor Swing Diameter</b>	17"
<b>Rotor Shaft Speed</b>	220 rpm at 540 rpm PTO
<b>PTO Driveline</b>	ASAE Category 3 Slip clutch
<b>Gearbox</b>	55 HP, 540 rpm, Cast Iron Housing, Drain Plug
<b>Drive Chain</b>	#100 high tensile in oil bath
<b>Sprockets</b>	Splined Bores

\* See dealer for complete warranty information.

Tilling depth depends on conditions and fluffiness of tilled area.

**Color Options:**



**3 YEAR**  
Limited Gearbox  
Warranty

- Spring-loaded rear deflector levels the freshly tilled seedbed
- Hinged front flap with rubber insert helps prevent damage to deck from debris coming over the top of the tines
- Skid shoe on drive side has additional chain case protection

Sifting tines help 'sift' the tilled material. Large or clumpy material fall first, with the top layer being a perfect consistency for planting.



Rear deflector removed for photo.



## Save time with reverse rotation.

Ground cover in your way? No problem for a Reverse Tine Tiller. It turns it up, chops it a time or two, and buries it under a cascade of large clods, which are buried under small clods. Large clods fall first, and they just get smaller as they pile on top of each other. What's left on top is a perfect seedbed to foster your wild imagination!



The reverse rotation of the tiller tines forces the tiller in the ground, preventing "walking" on hard ground. Once it's in, it stays put!

