

GRADING SCRAPERS



Ideal for renovating gravel driveways and roads, leveling construction and turf sites, and cleaning barns and chicken coops.



GS15 Series

25-50 HP

GS1548, GS1560, GS1572

Cat. 1

| | |
|-------------------------------------|---------------------------------------------------------------------------------|
| Working Width (cm) | 48" (122), 60" (152), 72" (184) |
| Side Panel Thickness | 3/16" thick with 2-3/4" formed edges |
| Front Main Beam & Scarifier Support | 4" x 4" x 5/16" reinforced heavy wall tubing |
| Rear Beam Construction | 2" x 2" x 3/16" heavy wall tubing |
| Skid Shoe Dimensions | 3/8" thick x 2-3/4" wide x 44" long |
| Scarifier Shank Construction | Heat treated 4-position shank with dimpled-on hardened tips |
| Cutting Edges | Two 1/2" x 6" high carbon heat treated blades that are reversible & replaceable |
| Cutting Edge Adjustment | Infinite vertical adjustment from level grade to 1-1/2" below grade |
| Weight w/Shanks -lb (kg) | 437 (198), 511 (232), 594 lbs. (269) |

Color Options:



GS25 Series

40-90 HP

GS2584, GS2596

Cat. 1 & 2

| | |
|-------------------------------------|-----------------------------------------------------------------------------------|
| Working Width (cm) | 84" (213), 96" (244) |
| Side Panel Thickness | 1/4" Thick with 2-3/4" formed edges |
| Front Main Beam & Scarifier Support | 4" x 4" x 5/16" Reinforced heavy wall tubing 3" x 3" x 3/16" heavy wall tubing |
| Skid Shoe Dimensions | 3/8" Thick x 2-3/4" wide x 50-1/4" long |
| Scarifier Shank Construction | Heat treated 4-position shank with dimpled-on hardened tips |
| Cutting Edges | Two 1/2" x 6" high carbon heat treated blades that are reversible & replaceable |
| Cutting Edge Adjustment | Infinite vertical adjustment from level grade to 1-1/2" below grade |
| Weight - lb (kg) | 822 (373), 890 (404) |

Color Options:

