

Landscape Rakes

LR25 Series

| Features | Benefits |
|---|--|
| Working widths | 84", 96" |
| HP Range | 25-50 HP |
| Fits Land Pride Quick-Hitch | Allows for quick and easy one person hook-up. |
| Angle 7 forward positions and 5 reverse positions | Vary amount of material to move. |
| Optional hydraulic angle cylinder | Change the rake angle on the go from the tractor seat. |
| 16 " Rake height | Allows for moving a great deal of material. |
| High carbon spring steel teeth | Allows teeth to keep their shape. |
| Individually replaceable teeth | Makes replacement easy and quick. |
| Retractable Parking Stand | Keeps the frame off the ground and makes hook-up easier. |
| Single or dual gauge wheels (optional) | Depth control. |
| Flip-down grader blade and end plates (optional) | Allows rake to be used for leveling by being able to scrape and drag material. |
| Blade adaptable | Adds versatility. Replace Rake elements with moldboard. |
| Warranty | One year parts & labor. |

LR35 Series

| Features | Benefits |
|--|---|
| Working widths | 84", 96" |
| Tractor HP Range | 30-65 HP |
| Cat. I & II | Fits a wider variety of tractors. |
| Fits Land Pride Quick-Hitch | Allows for quick and easy one person hook-up. |
| Frame offsets 45 degrees manually or hydraulically | Easily cover one tractor tire track. Optional hydraulic provided control from the tractor seat. |
| Angle 9 forward positions and 5 reverse positions | Vary the amount of material being moved. |
| 16 1/2" Rake height | Can move a great deal of material. |
| High carbon spring steel teeth | 84" width = 42 teeth 96" width = 48 teeth Allows teeth to keep their shape. |
| Individually replaceable teeth | Quick and easy replacement. |
| Retractable Parking Stand | Keeps the frame off the ground and makes hook-up easier. |
| Rear Blade adaptable | Get more out of a rake investment. |
| Single or dual gauge wheels (optional) | Provide better depth control. |
| Flip-down grader blade and side plates (optional) | Enables the rake to perform light blading duties and can be flipped up when not in use. |
| Warranty | One year parts & labor. |

Designs, specifications, features and information are subject to change without notice.