

**Built tough . . .
where it really counts.**

**Make
changes
On The Go**
with our 3-Way
Hydraulic
Rear Blades

RBT45 Series

**70-125 HP
RBT4596, RBT45108
Cat. 2 & 3**

Working Width (cm)	96" (244), 108" (274)
Weight - lb (kg)	1130 (513), 1166 (529)
Maximum G.V.W. - lb (kg)	15,000 (6818)
Blade Angle	15 Positions (Manual): 15°, 30° & 45°
Angle Cylinder	4" x 16"
Tilt	Up to 15°
Tilt Cylinder	3" x 6" x 1-1/4"
Swing Offset	Up to 35° Left and Right
Offset Cylinder	4" x 16"
Moldboard Height	19"
Moldboard Thickness	5/16" with 1/4" Boxed Reinforcement
Cutting Edge	1/2" x 6" Heat Treated
Options	Skid Shoes, End Plates, Hardened Wear Plates, Single or Dual Gauge Wheel, Cushion Valve, Double Selector Valve

Color Options:



RBT55 Series

**90-180 HP
RBT55120
Cat. 2 & 3**

Working Width (cm)	120" (304)
Weight - lb (kg)	1,753 (795)
Maximum G.V.W. - lb (kg)	15,000 (6818)
Blade Angle	15 Positions (Manual): Forward & Rev. Up to 45°
Tilt	Up to 30°
Tilt Cylinder	3-1/2" x 8" x 1-1/4"
Swing Offset	33°
Offset Cylinder	4-1/2" x 16" x 2"
Moldboard Height	19"
Moldboard Thickness	5/16" Reinforced
Cutting Edge	1/2" x 6" Reversible & Double Bevel, Heat Treated
Options	Skid Shoes, End Plates, Hardened Wear Plates, Hydraulic Single Gauge Wheel, Hydraulic Dual Gauge Wheel, Double Selector Valve

Color Options:



RBT55 pivot weldment features a
1" plate steel turntable, 1/2" thick tilt pivot
bushing and a 4" solid kingpin.



Optional cushion valve protects
cylinders and blade components
during extreme impacts. For use
on RBT40 & 45 Models.



Optional single or dual
gauge wheels add
accuracy and simplify
grading operations.

Shown with
optional end
plates.

