Prepare soil quickly while reducing the labor.

The Skid Steer Mounted Powered Rake can clean up construction sites, tear out unwanted growth, level and grade, and work up the soil to leave a picture perfect seedbed. Designed to attach to most late model skid steer units, a





Height adjustment is simple on the air-filled gauge wheels and allows for perfect results in a variety of soils.

Carbide-tipped, studded roller does an excellent job removing old growth, as well as pulverizing clods to a consistent size.

SR26 Series

72": 11 GPM @2200 psi 90": 15 GPM @2500 psi SR2672, SR2690 Skid Steer Plate or Front Loader Hitch

Working Width 90" (228)

Material Control Deflector 2 each - 1/2" x 5" Hard

(cm) Urethane (1.27 x 12.70)

Roller 9-3/8" Diameter with 3/4" x 1-1/2"

Carbide Tipped Studs

Roller Speed Variable from 180 to

260 RPM

Drive Chain #50 Double Continuous

Roller Chain, High Tensile, Enclosed in Oil Bath

Angle Adjustment 22° Left, 18° Right,

Forward or Reverse

Angle Cylinder 2" x 8"

Gauge Wheels 16.5" x 6.5" Air Tires with

Sealant and 3/4" Roller Bearings and Spacer Height Adjustment

Skid Shoes Replaceable

Machine Weight - Ib (kg) 930 (422), 1,020 (463)

Color Options:







End panels are conveniently stored out of the way when not in use.